



RECOMMEND P.C.B. LAYOUT  
TOLERANCE ±0.05  
TOP VIEW

## MATERIALS

1. HOUSING : HI.-TEMP.PLASTIC(UL 94V-0).BLACK
2. TERMINAL : COPPER ALLOY.(t=0.15mm)  
GOLD PLATED OVER NICKEL

## SPECIFICATION

1. CURRENT RATING : 1.0 A MAX.
2. DIELECTRIC WITHSTANDING VOLTAGE :  
500V AC R.M.S. FOR ONE MINUTE.
3. INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC.
4. CONTACT RESISTANCE : 30mΩ MAX.
5. OPERATING TEMPERATURE : -40°C TO +85°C.

115D-A A X 0-R  
1 2 3 4

1.Type

A: 6Pin

2.Contact Plating

A:15u"Gold Plating

3.Height

A:2.6mm

B:2.2mm

C:2.0mm

D:1.9mm

E:1.8mm

4.RoHS

UNLESS OTHERWISE  
SPECIFIED TOLERANCE

ANG. ±5  
0. ±0.3  
.0 ±0.25  
.00 ±0.20

SCALE: AS SHOWN UNIT: mm

DRAWN Willis 2009/01/06

CHECKED / /

APPROVED / /

DATE SIZE A4 REV.



ATTEND TECHNOLOGY INC.

www.attend.com.tw

DRAWN NAME:  
SIM Card Socket  
6Pin w/Height w/o Card Holder

PRODUCT NO. 115D-AAx0-R

FILE NAME: 115D-AAx0-R

REV.	DESCRIPTION	DATE	SIZE	REV.
1			A4	